

### T 5 (Teilung = 5,0 mm)

Artikel-Nr. Ketten Fuchs	Wirk- länge in mm	Zähne- zahl	Standardbreiten in mm						
			(Bitte ausgewählte Breite vor Art.-Nr. setzen)						
			6	8	10	12	16	20	25
T5-675	675,0	135	6	8	10	12	16	20	25
T5-690	690,0	138	6	8	10	12	16	20	25
T5-700	700,0	140	6	8	10	12	16	20	25
T5-720	720,0	144	6	8	10	12	16	20	25
T5-725	725,0	145	6	8	10	12	16	20	25
T5-750	750,0	150	6	8	10	12	16	20	25
T5-765	765,0	153	6	8	10	12	16	20	25
T5-780	780,0	156	6	8	10	12	16	20	25
T5-800	800,0	160	6	8	10	12	16	20	25
T5-815	815,0	163	6	8	10	12	16	20	25
T5-830	830,0	166	6	8	10	12	16	20	25
T5-840	840,0	168	6	8	10	12	16	20	25
T5-850	850,0	170	6	8	10	12	16	20	25
T5-860	860,0	172	6	8	10	12	16	20	25
T5-885	885,0	177	6	8	10	12	16	20	25
T5-900	900,0	180	6	8	10	12	16	20	25
T5-920	920,0	184	6	8	10	12	16	20	25

Artikel-Nr. Ketten Fuchs	Wirk- länge in mm	Zähne- zahl	Standardbreiten in mm						
			(Bitte ausgewählte Breite vor Art.-Nr. setzen)						
			6	8	10	12	16	20	25
T5-940	940,0	188	6	8	10	12	16	20	25
T5-990	990,0	198	6	8	10	12	16	20	25
T5-1075	1075,0	215	6	8	10	12	16	20	25
T5-1100	1100,0	220	6	8	10	12	16	20	25
T5-1160	1160,0	232	6	8	10	12	16	20	25
T5-1200	1200,0	240	6	8	10	12	16	20	25
T5-1215	1215,0	243	6	8	10	12	16	20	25
T5-1275	1275,0	255	6	8	10	12	16	20	25
T5-1280	1280,0	256	6	8	10	12	16	20	25
T5-1315	1315,0	263	6	8	10	12	16	20	25
T5-1355	1355,0	271	6	8	10	12	16	20	25
T5-1380	1380,0	276	6	8	10	12	16	20	25
T5-1440	1440,0	288	6	8	10	12	16	20	25
T5-1470	1470,0	294	6	8	10	12	16	20	25
T5-1500	1500,0	300	6	8	10	12	16	20	25
T5-1580	1580,0	316	6	8	10	12	16	20	25
T5-1955	1955,0	391	6	8	10	12	16	20	25

Riemengewicht = 2,2 × g/m × Breite in mm

### T 10 (Teilung = 10,0 mm)

Artikel-Nr. Ketten Fuchs	Wirk- länge in mm	Zähne- zahl	Standardbreiten in mm							
			(Bitte ausgewählte Breite vor Art.-Nr. setzen)							
			10	12	16	20	25	32	50	75
T10-260	260,0	26	10	12	16	20	25	32	50	75
T10-320	320,0	32	10	12	16	20	25	32	50	75
T10-340	340,0	34	10	12	16	20	25	32	50	75
T10-370	370,0	37	10	12	16	20	25	32	50	75
T10-390	390,0	39	10	12	16	20	25	32	50	75
T10-400	400,0	40	10	12	16	20	25	32	50	75
T10-410	410,0	41	10	12	16	20	25	32	50	75
T10-440	440,0	44	10	12	16	20	25	32	50	75
T10-450	450,0	45	10	12	16	20	25	32	50	75
T10-480	480,0	48	10	12	16	20	25	32	50	75
T10-500	500,0	50	10	12	16	20	25	32	50	75
T10-530	530,0	53	10	12	16	20	25	32	50	75
T10-550	550,0	55	10	12	16	20	25	32	50	75
T10-560	560,0	56	10	12	16	20	25	32	50	75
T10-600	600,0	60	10	12	16	20	25	32	50	75
T10-610	610,0	61	10	12	16	20	25	32	50	75
T10-630	630,0	63	10	12	16	20	25	32	50	75
T10-650	650,0	65	10	12	16	20	25	32	50	75
T10-660	660,0	66	10	12	16	20	25	32	50	75
T10-680	680,0	68	10	12	16	20	25	32	50	75
T10-690	690,0	69	10	12	16	20	25	32	50	75
T10-700	700,0	70	10	12	16	20	25	32	50	75
T10-720	720,0	72	10	12	16	20	25	32	50	75
T10-730	730,0	73	10	12	16	20	25	32	50	75
T10-750	750,0	75	10	12	16	20	25	32	50	75
T10-780	780,0	78	10	12	16	20	25	32	50	75
T10-800	800,0	80	10	12	16	20	25	32	50	75
T10-810	810,0	81	10	12	16	20	25	32	50	75
T10-840	840,0	84	10	12	16	20	25	32	50	75
T10-850	850,0	85	10	12	16	20	25	32	50	75
T10-880	880,0	88	10	12	16	20	25	32	50	75
T10-890	890,0	89	10	12	16	20	25	32	50	75
T10-900	900,0	90	10	12	16	20	25	32	50	75
T10-910	910,0	91	10	12	16	20	25	32	50	75
T10-920	920,0	92	10	12	16	20	25	32	50	75

Artikel-Nr. Ketten Fuchs	Wirk- länge in mm	Zähne- zahl	Standardbreiten in mm							
			(Bitte ausgewählte Breite vor Art.-Nr. setzen)							
			10	12	16	20	25	32	50	75
T10-950	950,0	95	10	12	16	20	25	32	50	75
T10-960	960,0	96	10	12	16	20	25	32	50	75
T10-970	970,0	97	10	12	16	20	25	32	50	75
T10-980	980,0	98	10	12	16	20	25	32	50	75
T10-1000	1000,0	100	10	12	16	20	25	32	50	75
T10-1010	1010,0	101	10	12	16	20	25	32	50	75
T10-1050	1050,0	105	10	12	16	20	25	32	50	75
T10-1080	1080,0	108	10	12	16	20	25	32	50	75
T10-1100	1100,0	110	10	12	16	20	25	32	50	75
T10-1110	1110,0	111	10	12	16	20	25	32	50	75
T10-1140	1140,0	114	10	12	16	20	25	32	50	75
T10-1150	1150,0	115	10	12	16	20	25	32	50	75
T10-1200	1200,0	120	10	12	16	20	25	32	50	75
T10-1210	1210,0	121	10	12	16	20	25	32	50	75
T10-1240	1240,0	124	10	12	16	20	25	32	50	75
T10-1250	1250,0	125	10	12	16	20	25	32	50	75
T10-1300	1300,0	130	10	12	16	20	25	32	50	75
T10-1320	1320,0	132	10	12	16	20	25	32	50	75
T10-1350	1350,0	135	10	12	16	20	25	32	50	75
T10-1390	1390,0	139	10	12	16	20	25	32	50	75
T10-1400	1400,0	140	10	12	16	20	25	32	50	75
T10-1420	1420,0	142	10	12	16	20	25	32	50	75
T10-1440	1440,0	144	10	12	16	20	25	32	50	75
T10-1450	1450,0	145	10	12	16	20	25	32	50	75
T10-1460	1460,0	146	10	12	16	20	25	32	50	75
T10-1500	1500,0	150	10	12	16	20	25	32	50	75
T10-1560	1560,0	156	10	12	16	20	25	32	50	75
T10-1600	1600,0	160	10	12	16	20	25	32	50	75
T10-1610	1610,0	161	10	12	16	20	25	32	50	75
T10-1700	1700,0	170	10	12	16	20	25	32	50	75
T10-1750	1750,0	175	10	12	16	20	25	32	50	75
T10-1780	1780,0	178	10	12	16	20	25	32	50	75
T10-1880	1880,0	188	10	12	16	20	25	32	50	75
T10-1960	1960,0	196	10	12	16	20	25	32	50	75
T10-2250	2250,0	225	10	12	16	20	25	32	50	75

Riemengewicht = 4,4 × g/m × Breite in mm