

8M (Teilung = 8,0 mm)

Artikel-Nr. Ketten Fuchs	Wirk- länge in mm	Zähne- zahl	Standardbreiten in mm			
			(Bitte ausgewählte Breite vor Art.-Nr. setzen)			
			20	30	50	85
288-8M	288,0	36	20	30	50	85
320-8M	320,0	40	20	30	50	85
352-8M	352,0	44	20	30	50	85
360-8M	360,0	45	20	30	50	85
384-8M	384,0	48	20	30	50	85
408-8M	408,0	51	20	30	50	85
416-8M	416,0	52	20	30	50	85
456-8M	456,0	57	20	30	50	85
480-8M	480,0	60	20	30	50	85
536-8M	536,0	67	20	30	50	85
544-8M	544,0	68	20	30	50	85
560-8M	560,0	70	20	30	50	85
600-8M	600,0	75	20	30	50	85
608-8M	608,0	76	20	30	50	85
632-8M	632,0	79	20	30	50	85
640-8M	640,0	80	20	30	50	85
680-8M	680,0	85	20	30	50	85
720-8M	720,0	90	20	30	50	85
760-8M	760,0	95	20	30	50	85
800-8M	800,0	100	20	30	50	85
840-8M	840,0	105	20	30	50	85
880-8M	880,0	110	20	30	50	85
896-8M	896,0	112	20	30	50	85
920-8M	920,0	115	20	30	50	85
960-8M	960,0	120	20	30	50	85
1000-8M	1000,0	125	20	30	50	85

Riemengewicht = 5,69 × g/m × Breite in mm

14M (Teilung = 14,0 mm)

Artikel-Nr. Ketten Fuchs	Wirk- länge in mm	Zähne- zahl	Standardbreiten in mm				
			(Bitte ausgewählte Breite vor Art.-Nr. setzen)				
			40	55	85	115	170
66-14M	966,0	69	40	55	85	115	170
994-14M	994,0	71	40	55	85	115	170
1092-14M	1092,0	78	40	55	85	115	170
1106-14M	1106,0	79	40	55	85	115	170
1190-14M	1190,0	85	40	55	85	115	170
1260-14M	1260,0	90	40	55	85	115	170
1288-14M	1288,0	92	40	55	85	115	170
1344-14M	1344,0	96	40	55	85	115	170
1400-14M	1400,0	100	40	55	85	115	170
1442-14M	1442,0	103	40	55	85	115	170
1568-14M	1568,0	112	40	55	85	115	170
1610-14M	1610,0	115	40	55	85	115	170
1750-14M	1750,0	125	40	55	85	115	170
1764-14M	1764,0	126	40	55	85	115	170
1778-14M	1778,0	127	40	55	85	115	170
1848-14M	1848,0	132	40	55	85	115	170
1890-14M	1890,0	135	40	55	85	115	170
1904-14M	1904,0	136	40	55	85	115	170

Riemengewicht = 11,58 × g/m × Breite in mm

Artikel-Nr. Ketten Fuchs	Wirk- länge in mm	Zähne- zahl	Standardbreiten in mm			
			(Bitte ausgewählte Breite vor Art.-Nr. setzen)			
			20	30	50	85
1040-8M	1040,0	130	20	30	50	85
1080-8M	1080,0	135	20	30	50	85
1120-8M	1120,0	140	20	30	50	85
1200-8M	1200,0	150	20	30	50	85
1224-8M	1224,0	153	20	30	50	85
1280-8M	1280,0	160	20	30	50	85
1352-8M	1352,0	169	20	30	50	85
1424-8M	1424,0	178	20	30	50	85
1440-8M	1440,0	180	20	30	50	85
1464-8M	1464,0	183	20	30	50	85
1600-8M	1600,0	200	20	30	50	85
1680-8M	1680,0	210	20	30	50	85
1760-8M	1760,0	220	20	30	50	85
1800-8M	1800,0	225	20	30	50	85
1904-8M	1904,0	238	20	30	50	85
2000-8M	2000,0	250	20	30	50	85
2200-8M	2200,0	275	20	30	50	85
2272-8M	2272,0	284	20	30	50	85
2400-8M	2400,0	300	20	30	50	85
2520-8M	2520,0	315	20	30	50	85
2600-8M	2600,0	325	20	30	50	85
2800-8M	2800,0	350	20	30	50	85
3048-8M	3048,0	381	20	30	50	85
3280-8M	3280,0	410	20	30	50	85
3600-8M	3600,0	450	20	30	50	85
4400-8M	4400,0	550	20	30	50	85